

LP202 Series

Loop Power Sensor, 4-20 mA Output Proportional to Vibration in Velocity, Top Exit 2 Pin Connector



VIBRATION ANALYSIS HARDWARE



Product Features

Continuously Monitor & Protect Important Machinery

- ▶ 4-20 mA current proportional to Vibration
- ▶ Transmit Signals Over Long Distances with No Signal Loss
- ▶ Customize Your Settings to Focus on the Most Important Frequencies

LP202-XXX-1E 2 Pin Connector	LP202-XXX-2E CB103 Integral Cable	LP202-XXX-3E CB206 Armored Integral Cable																						
<table border="1"> <thead> <tr> <th>Connector Pin</th> <th>Polarity</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>(+) Loop Power mA Output</td> </tr> <tr> <td>B</td> <td>(-) Common</td> </tr> </tbody> </table> <p>Built To Order</p>	Connector Pin	Polarity	A	(+) Loop Power mA Output	B	(-) Common	<table border="1"> <thead> <tr> <th>Conductor</th> <th>Polarity</th> </tr> </thead> <tbody> <tr> <td>Red</td> <td>(+) Loop Power mA Output</td> </tr> <tr> <td>Black</td> <td>(-) Common</td> </tr> <tr> <td>Shield</td> <td>Cable Drain Wire</td> </tr> </tbody> </table> <p>Built To Order</p>	Conductor	Polarity	Red	(+) Loop Power mA Output	Black	(-) Common	Shield	Cable Drain Wire	<table border="1"> <thead> <tr> <th>Conductor</th> <th>Polarity</th> </tr> </thead> <tbody> <tr> <td>Red</td> <td>(+) Loop Power mA Output</td> </tr> <tr> <td>Black</td> <td>(-) Common</td> </tr> <tr> <td>Shield</td> <td>Cable Drain Wire</td> </tr> </tbody> </table> <p>Built To Order</p>	Conductor	Polarity	Red	(+) Loop Power mA Output	Black	(-) Common	Shield	Cable Drain Wire
Connector Pin	Polarity																							
A	(+) Loop Power mA Output																							
B	(-) Common																							
Conductor	Polarity																							
Red	(+) Loop Power mA Output																							
Black	(-) Common																							
Shield	Cable Drain Wire																							
Conductor	Polarity																							
Red	(+) Loop Power mA Output																							
Black	(-) Common																							
Shield	Cable Drain Wire																							

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	LP202	M/LP202	Physical		
Tolerance: 4 mA	(± 10%)		Sensing Element	PZT Ceramic	
Tolerance: 20 mA	(± 10%)		Sensing Structure	Shear Mode	
Electrical			Weight	2.9 oz	82 grams
Settling Time	<30 Seconds		Case Material	316L Stainless Steel	
Voltage Source (IEPE)	15-30 VDC		Mounting	1/4-28	
Case Isolation	>10 ⁸ ohm		Connector (Non-Integral)	2 Pin MIL-C-5015	
Environmental			Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Temperature Range	-40 to 212°F	-40 to 100°C	Mounting Hardware	1/4-28 Stud	M6x1 Adapter Stud
Electromagnetic Sensitivity	CE		Calibration Certificate	Current Output @ 100 Hz	
Sealing	Welded, Hermetic				
Submersible Depth	200 ft.	60 m			

Ordering Information

Stud Type	Measurement Range	Type	Frequency Range ±3dB	Style	Integral Options	
Blank = 1/4-28 M = M6x1	0 = 0-0.5 IPS (0-12.7 mm/sec) 1 = 0-1 IPS (0-25.4 mm/sec) 2 = 0-2 IPS (0-50.8 mm/sec) 3 = 0-0.4 IPS (0-10 mm/sec) 4 = 0-0.8 IPS (0-20 mm/sec) 6 = 0-5 IPS (0-127 mm/sec)	P = Peak R = RMS	1 = 600-60000 CPM (10-1000 Hz) 2 = 180-150000 CPM (3-2500 Hz) 3 = 180-60000 CPM (3-1000 Hz) 4 = 180-300000 CPM (3-5000 Hz) 5 = 180-600000 CPM (3-10000 Hz)	1E = 2 Pin MIL C-5015 2E = Integral Cable 3E = Armor Jacket M12E = 4 Pin M12	Armor Length (Integral) 010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m	Cable Length (Integral) 010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m

*Custom Lengths Available Upon Request

Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900